## **Richmond Hill Boom Lift License**

Richmond Hill Boom Lift License - To be able to operate an aerial boom lift, operators must be qualified through training that could be obtained utilizing both classroom sessions and practical training and by attaining a boom lift license. Instruction must be given with respect to the type of aerial lift which would be used on the job. A License is required for any individual who operates or works on an aerial boom lift.

Different kinds of vehicle-mounted aerial devices consist of aerial ladders, extensible boom platforms, vertical towers, articulating boom platforms, and any combination of these kinds.

There are a number of basic safety rules which apply to all boom lifts. Worker safety while within the basket is a top priority. Workers should put on a body harness and lanyard attached to the boom or basket. Never tie off to an adjacent pole, structure, or equipment. Personnel should stand on the floor of the basket, and never climb or sit on the edge of the basket. The load limits of the manufacturer must be adhered to.

Aerial lift operators must be authorized to make use of the equipment. The operator needs to be familiar with all the aspects of the device and must have access to the manufacturers instruction manual which must be kept in the lift. Operators are responsible for ensuring that safety measures are followed in operating the lift. A daily test of lift controls should be performed. Position outriggers and set brakes (if they are utilized) on pads or a stable surface. If working on a slope, use wheel chocks.

Never move an aerial lift truck with an elevated boom whilst workers are inside the basket. Extensible boom platforms and articulating boom made use of as employees carriers must have accessible, plainly marked, upper controls. Except for in emergency conditions, lower controls should not be used to override upper controls unless authorization has been given by the person within the lift.

While working from an aerial lift, do not wear pole or tree climbers.

The insulated part of the aerial lift should not be altered.

Ensure that the booms are thoroughly checked, that the machine is correctly cradled and the outriggers are in the stowed position before moving.

When operating a boom lift next to power lines, make certain that the lines are di-electrically tested according to local rules.